

## PERFORATED SLEEVES MM. 500 LONG in Vulkollan® 65, 80 or 92 Sh°A



### External Diameter (mm)

21.60	25.30	31.20	31.40	33.90	34.30	38.00
38.20	41.20	44.10	44.60	47.00	50.50	51.00
53.80	57.60	57.80	62.70	63.70	67.60	68.60
70.60	73.50	75.90	77.90	81.10	92.60	96.50
101.90	102.40	112.70	123.00	129.40	150.90	156.00
159.70						

### Internal Diameter (mm)

8.05	8.85	9.00	9.45	9.75	9.85	10.00
10.25	10.35	11.80	12.20	13.70	13.80	14.80
15.45	15.95	16.25	17.05	19.50	19.70	20.10
20.20	20.60	21.10	21.20	22.05	22.15	22.95
23.65	23.85	25.00	25.10	25.30	25.50	25.80
26.00	27.95	28.05	28.15	29.55	30.25	32.00
32.50	35.35	37.15	38.00	38.40	38.80	40.40
44.35	46.80	48.25	49.55	57.15	57.45	58.10
59.80	62.90	64.50	79.40			

Note: It is possible to combine all the internal diameters with the external ones. However, it is required a minimum difference of 10mm between the two diameters.

## RODS/FULL BARS MM. 200 LONG in Vulkollan® 65, 80 or 92 Sh°A



### External Diameter (mm)

13.80	16.20	16.50	19.00	21.20	23.50	25.50
-------	-------	-------	-------	-------	-------	-------

## RODS/FULL BARS MM. 500 LONG in Vulkollan® 65, 80 or 92 Sh°A



### External Diameter (mm)

9.80	10.80	14.70	15.70	17.60		
81	92	96	103	112	124	131
151	160					

## RODS/FULL BARS MM. 1000 LONG in Vulkollan® 92 Sh°A



### External Diameter (mm)

14.7	17.6	18.6	19.6	20.6	21.5	22.5
23.5	24.5	25	25.5	26.4	27.4	31.3
36.2	41.1	45	47	50.9	52.8	58.7
62.6	63.5	70.5				